



TACTILE

T100 (GUIDANCE TILE)

T200 (STUDED TILE)

Product Specifications

Feature	Standard	Results	Notes	
Safety				
Halogen Free		Yes		
Asbestos Free		Yes		
This product does not contain PVC, cadmium, formaldehyde, chlorine, fluorine or bromine, which could be highly toxic and corrosive in case of fire.				
Fire and Smoke Behaviour				
Critical Heat Flux Critical Radiant Flux	ASISO 9239.1-2003	≥ 11 kw/m ²		
Smoke Value	ASISO9239.1-2003	16 min		
Toxicity of Smoke	Boeing Safety Standard BSS 7239	ppm level (Complies)		
Mechanical Features				
Hardness	ASTM D-2240	≥ 85 Shore A	Complies with ADA	
Dimensional Stability	DIN 51962	< 0.3 % No variation		
Indentation	ASTM F-36	≤ 0.20 mm		
Abrasion Resistance	DIN 53516	≤ 160 mm ³		
Elongation	ASTM D412	~150 %		
Tensile Strength	ASTM D-412	≥ 800 psi		
Slip Resistance	ASTM D-2047-82	≥0.60		
Resistance to Elements Over Time				
Colour Fastness	DIN 53389	5 - 7		See Chart
Water Retention	ASTM D471	≤ 1 %		
Chemical Resistance	DIN 51958	Good		
Cigarette Burn Resistance	DIN 51961	Yes	Visual Judgment	
Acoustical Features				
Acoustical Insulation	DIN 52210	~ 10 dB	Noise abetment	
Electrical Features				
Insulation	DIN 53596	≥ 10 ¹⁰ ohm	Insulating	
Static Generation	DIN 54345	<2 kV	Antistatic	
Composition				
ACTIVA Rubber flooring products are made of 100% synthetic rubber (SBR - Styrene Butadiene Rubber), the finest quality minerals, organic stabilising agents, vulcanising agents, antioxidants and quality pigments. They DO NOT CONTAIN re-ground rubber, coarse mineral aggregates, fillers, sand or any material known to pose a health hazard in any of the phases of the manufacturing and use cycle.				

Product Description

TACTILE™ Ground surface
Indicator Rubber complies with AS 1428.4

Features

- Easy Maintenance
- Slip Resistant
- Sound Absorbent
- High durability Compound
- Highly Resilient

Environmental & Safety

Product FREE from:
Halogens, Antimony, Arsenic, Barium, Lead, Cadmium, Chromium, PVC, Volatile elements, DOP's, Formaldehyde, Asbestos and Heavy metals.
Manufactured in compliance with ISO 14001

Information

- Tile Size : 300 x 300 mm
 - Total Thickness :7.0 mm
 - Base Thickness : 2.0 mm
 - Limited Wear Warranty: 1 Year
 - Colour : 4 Standard Colours
- Recommended Adhesives:
Two-part PU
**Please consult our office for detail.*

PRF (NZ) Pty Ltd.
6 Findlay Street
Ellerslie, Auckland
P: (09) 579 2890 F:(09) 579 2892
www.rubberflooring.co.nz